REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED







MODEL	TLTS P/N	CAPACITY (lbs-in)
12328-10K	160289	10,000
12328-20K	160291	20,000
12328-50K	160294	50,000

SPECIFICATIONS

OUTPUT @ RATED LOAD: 2 NOMINAL
ZERO BALANCE: ±1%
BRIDGE RESISTANCE: 350 OHMS
TEMPERATURE COMPENSATED RANGE: +70˚F TO 150˚F
TEMPERATURE EFFECT ON ZERO: 0.0025%
EXCITATION VOLTAGE MAX: 10 VDC

PROPRIETARY AND CONFIDENTIAL
THIS INFORMATION IS PROPRIETARY TO TELEDYNE LECROY TEST SERVICES AND IS PROVIDED FOR THE SOLE PURPOSE OF EVALUATING TECHNICAL COMPATIBILITY OF THE DESIGN WITH INTENDED APPLICATIONS. THIS INFORMATION MAY NOT BE USED FOR ANY OTHER PURPOSE AND MAY NOT BE DISCLOSED TO ANY OTHER PARTIES WITHOUT PRIOR WRITTEN PERMISSION.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES ON:
FRACTIONAL: ±1/64
ANGULAR: ± 2 Degrees
TWO PLACE DECIMAL: ±.010
THREE PLACE DECIMAL: ±.005
INTERPRET GEOMETRIC TOLERANCING PER:
MATERIAL -
FINISH 125

	NAME	DATE
DRAWN	KWL	6/5/17
CHECKED		
ENG APPR.		
Q.A.		

PROJECT NO. -

TELEDYNE
LECROY TEST SERVICES
Everywhere You Look
513 Mill St., Marion, MA 02738
Tel.: (508) 748-0103 Fax: (508) 748-2029

TITLE:
REACTION TORQUE SENSOR ASSEMBLY

SIZE	DWG. NO.	REV
B	12328-ASSY-2	0

SCALE: 1:2 | WEIGHT: | SHEET 1 OF 1